



CLARCOR Air Filtration Products
 P.O. Box 32578
 Louisville KY 40232
 Customer Care Team 1-866-925-2247
 Fax 1-800-784-3458

CARBON SIDE ACCESS FILTER HOUSING (CSA)

DATE _____

APPROVED APPROVED AS NOTED

SIGNATURE _____

MODEL NUMBER _____

Prefilter only tracks are available for 2" or 4" filters.

Woven Nylon Seal

CARBON BED

CARBON BED

PREFILTER

PREFILTER

Carbon track is designed to hold 1" nominal deep filters.

EXTRUSION DETAIL

PREFILTER DEPTH (SELECT ONE)

A = 2" Prefilter w/ 1" Final Filter Track

B = 4" Prefilter w/ 1" Final Filter Track

HOUSING DEPTH (SELECT ONE)

38" Depth (D)

DIMENSIONS HxW (SELECT ONE)

_____ H = Height (Inches)

_____ W = Width (Inches)

MATERIALS (SELECT ONE)

CA = 16 GA Galvanized Steel

CB = 16 GA 304 Stainless Steel

FACTORY OPTIONS

WC = Weathercap

DW = Double Wall Insulation (Includes Weathercap)

LL = Lifting Lugs, (4) Lugs Total

DF = Drilled Flanges _____ single / double

BA = Bottom Access

VF = Vertical Flow

SP = Static Pressure Ports, (2) Pair for Pre and Final Filter

SG = Static Pressure Gauge Not Installed (2 Gauges)

SI = Static Pressure Gauge Installed (2 Gauges/Pair of Ports)

T = Transition

O = Other (Specify on Submittal or Attachment)

SPECIFICATIONS

1. 16 GA Material Construction.
2. Extruded Aluminum Filter Tracks with Woven Nylon Pile Seal.
3. Doors Sealed with Closed Cell Neoprene Gasket.
4. Two Pound Density Urethane Foam Inside Access Doors Gaskets Filters.
5. Metal to Metal Components Sealed with Silicone Compound.
6. Doors Fitted with Quick Action, Positive Pressure Trip Lock Latches.
7. Doors on Both Sides.
8. Maximum Static Pressure 4.0" W.G. Positive or Negative

HOUSING DIMENSIONS

FULL SIZE FILTERS

HALF SIZE FILTERS

FULL SIZE TRAYS

HALF SIZE TRAYS

RATED AIR FLOW (CFM) @ 500 FPM

TOP VIEW

UPSTREAM VIEW

DOOR VIEW

AIR FLOW

DEPTH 36"

CARBON BED

PREFILTER TRACK

CORNER GUSSETS

VERTICAL SUPPORT

W

H

1 5/16

1 5/16