



Model Number	Nominal Size (Inches) W x H	Wire Size (Inches) W x H	Number Of Cross Wires	Initial Resistance (Inches W.G.)	
				300 FPM	500 FPM
ACT-217	10 x 20	9-1/2 x 19-1/2	1	.17	.35
ACT-210	12 x 24	11-3/8 x 23-3/8	2	.17	.35
ACT-245	15 x 20	14-1/2 x 19-1/2	1	.17	.35
ACT-201	16 x 20	15-1/2 x 19-1/2	1	.17	.35
ACT-216	16 x 24	15-3/8 x 23-3/8	2	.17	.35
ACT-202	16 x 25	15-1/2 x 24-1/2	2	.17	.35
ACT-212	18 x 24	17-3/8 x 23-3/8	2	.17	.35
ACT-261	20 x 16	19-1/2 x 15-1/2	1	.17	.35
ACT-203	20 x 20	19-1/2 x 19-1/2	1	.17	.35
ACT-211	20 x 24	19-3/8 x 23-3/8	2	.17	.35
ACT-204	20 x 25	19-1/2 x 24-1/2	2	.17	.35
ACT-206	24 x 12	23-3/8 x 11-3/8	1	.17	.35
ACT-244	24 x 16	23-3/8 x 15-3/8	1	.17	.35
ACT-215	24 x 20	23-3/8 x 19-3/8	1	.17	.35
ACT-205	24 x 24	23-3/8 x 23-3/8	2	.17	.35
ACT-165	25 x 16	24-1/2 x 15-1/2	1	.17	.35
ACT-252	25 x 20	24-1/2 x 19-1/2	1	.17	.35
ACT-225	25 x 25	24-1/2 x 24-1/2	2	.17	.35

STANDARD CONSTRUCTION:

1. Polyester Media With Tack
Blended Multi-Denier Media Layer Air Entering Side (White)
Needled Media Layer Air Leaving Side (White)
2. Heat Seal Construction
3. 9 GA Steel Internal Wire Frame
4. Cross Wires Installed in the Width Direction

NOTES:

1. MERV 6 ASHRAE 52.2-1999
2. Final Resistance: 1.0" W.G.
3. Class 2 Filter Per U.L. Standard 900
4. Maximum Operating Temperature: 220 deg. F



1612 N DAVIS AVE
OTTAWA, KS 66067
P: 800-624-8739
F: 785-242-8700

CONTACT FACTORY TO
VERIFY REVISION LEVEL

TOLERANCES
UNLESS OTHERWISE SPECIFIED

FRACTIONAL +/- 1/8"
DECIMAL -
ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

ACTIVATOR SERIES 2-PLY RING PANEL FILTER

APPROVED BY

K. Quinn

SPECIFICATION NO.

MKT-B-00450

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

A

REVISION DATE

11-15-06

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLARCOR AIR FILTRATION. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.