



MODEL NUMBER	NOMINAL SIZE WXHXD	ACTUAL SIZE WXHXD	CFM'S @ 500 FPM	INITIAL RESISTANCE	MEDIA AREA SQ.FT.
HE40I	12X24X2	11-3/8X23-3/8X1-3/4	1000	.36	5.5
HE40I	16X20X2	15-1/2X19-1/2X1-3/4	1100	.36	6.7
HE40I	16X25X2	15-1/2X24-1/2X1-3/4	1400	.36	8.4
HE40I	20X20X2	19-1/2X19-1/2X1-3/4	1400	.36	8.2
HE40I	20X25X2	19-1/2X24-1/2X1-3/4	1750	.36	10.3
HE40I	24X24X2	23-3/8X23-3/8X1-3/4	2000	.36	12.0
HE40I	12X24X4	11-3/8X23-3/8X3-3/4	1250	.40	10.2
HE40I	16X20X4	15-3/8X19-3/8X3-3/4	1400	.40	13.7
HE40I	16X25X4	15-3/8X24-3/8X3-3/4	1750	.40	17.2
HE40I	20X20X4	19-3/8X19-3/8X3-3/4	1750	.40	16.9
HE40I	20X25X4	19-3/8X24-3/8X3-3/4	2170	.40	21.2
HE40I	24X24X4	23-3/8X23-3/8X3-3/4	2500	.40	24.0

#### STANDARD CONSTRUCTION

1. High density ultra-fine fiberglass reinforced by a woven fiberglass mesh.
2. Expanded Metal Pleat Supports
3. Non-Flammable Board Frame
4. Double Wall Frame
5. High Temperature Adhesive
6. Finger Pleat Separators Included For 4" Depth

#### NOTES

1. Average Efficiency: 30-35% ASHRAE 52.1-1992 MERV 8 Rating
2. Final Resistance: 1.0" W.G.
3. Rated Velocity: 500 FPM 2" & 4" Depth
4. Class 1 Filter Per U.L. Standard 900
5. Maximum Operating Temperature: 200 deg. F


 P.O. Box 32578  
 Louisville, KY 40232  
 P: 866-925-2247  
 F: 502-961-0930  
 www.purolatorair.com

CONTACT FACTORY TO  
VERIFY REVISION LEVEL

#### TOLERANCES UNLESS OTHERWISE SPECIFIED

FRACTIONAL -  
 DECIMAL -  
 ANGLES -

ALL DIMENSIONS IN INCHES

DRAWING NAME

HE40I UL CLASS 1

APPROVED BY

*K. Clum*

SPECIFICATION NO.

MKT-P-00161

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

NEW

REVISION DATE

2-13-2008

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.